

Safety Data Sheet

Sintra®



Revision Date: 9/29/ 2017

Initial Release Date: 8/28/ 2002

Version 7.0

Section 1. Product Identification

Manufacturer: 3A Composites USA, Inc.
208 W. 5th Street, P.O. Box 507
Benton, KY 42025
(270) 527-4200

Emergency Phone Number: 1-800-424-9300 Chemtrec
To be used only in the event of chemical emergencies involving a spill, leak, fire, and exposure accidents involving chemicals.

Trade Name: Sintra® & E-PVC™

Synonym: Expanded PVC Sheet, Polyvinyl Chloride Sheet, Foamed PVC

Section 2. Hazard Identification

Physical Appearance: Medium weight rigid panel

Potential Health Effects:

This product is classified as a non-hazardous component when polymerized. Avoid breathing fumes if abraded, melted, welded, cut or processed.

Ingestion: Swallowing is not anticipated. If swallowed, seek immediate medical advice.

Label Elements - None

Signal Word: None

Pictogram: None

Hazard statements: None

Response Specific treatment- see supplemental first aid information.

Section 3. Chemical Composition

Ingredients:	CAS Number	Percent % (by weight) *
Polyvinyl Chloride	9002-86-2	75 – 90

Section 4. First Aid Measures

These products are not considered to be a health hazard in the form in which they are sold (sheet, panel). However, if these products are abraded, melted, welded, cut or processed in any manner that causes release of fumes or dusts, hazardous levels of fumes or dusts may be generated from these products.

Eye Contact: Dust may mechanically irritate the eyes, resulting in redness or watering. Treat dust in eye as foreign object. Flush with water to remove dust particles. Get medical help if irritation persists.

Skin Contact: Not anticipated for product in purchased form, wash with mild soap and water.

Inhalation: If inhalation causes adverse effects, respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard, 29 CFR 1920.134. Remove to fresh air. Get medical help if persistent irritation, severe coughing or breathing difficulty occurs.

Note to Physician: No special advice, treat symptomatically

Ingestion: Not likely to occur for product in purchased form.

Inhalation: Excessive dust concentrations may cause unpleasant obstruction in the nasal passages.

Skin Absorption: Product is not absorbed through the skin.

Section 5. Fire Fighting Measures

Extinguishing media: Water, foam, CO₂, dry chemical powder

Special firefighting procedure: Toxic gases may form upon combustion. Respiratory protection is recommended.

Unusual fire and explosion hazards: PVC will burn in the presence of supported combustion and will emit hydrogen chloride gas, benzene, water, carbon dioxide and smoke.

Because static sparking can occur during handling, all flammable materials should be removed from the immediate vicinity.

Section 6. Accidental Release

A release should not occur. However, if these products are abraded, melted or cut, dusts may be generated. Should a release of dusts occur, contain by blocking routes to surface water and grassy areas. Clean up by sweeping and depositing into a closed container.

Section 7. Handling and Storage

Store in a flat dry area. Handle carefully to avoid scratching product finish. Exercise caution in all thermal forming activities.

Section 8. Exposure Controls

These products are not considered to be a health hazard in the form in which they are sold (sheet, panel). However, if these products are abraded, melted, welded, cut or processed in any manner that causes release of fumes or dusts, hazardous levels of fumes or dusts may be generated from these materials or constituents of these materials. Aluminum fumes or dust are subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

RESPIRATORY PROTECTION – Not required. However, use NIOSH-approved filtering face piece respirator (“dust mask”) and goggles where ventilation is limited. Use respiratory protection in accordance with regulatory requirements such as the OSHA respiratory protection standard 29 CFR 1910.134.

PROTECTIVE GLOVES – Not required. However, cloth, canvas, or leather gloves are recommended to minimize potential mechanical irritation or cuts from handling product.

EYE PROTECTION – Approved goggles or tight fitting safety glasses are recommended when exposures to dust may occur (e.g. during clean up) and when eye irritation may occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT – Not applicable for product in purchased form. Outer garments may be desirable in extremely dusty areas.

WORK/HYGIENE PRACTICES – Follow good hygiene and housekeeping practices. Clean up areas where dust settles to avoid excessive accumulation. Minimize compressed air blow down or other practices that generate high airborne-dust concentrations.

Ventilation:

LOCAL EXHAUST – Provide local exhaust as needed so that exposure limits are met. Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation, and process enclosure if necessary, to control airborne dust. Ventilation to control dust should be considered where potential explosive concentrations and ignition sources are present. The design and operation of any exhaust system should consider the possibility of explosive concentrations of cellulose dust within the system. See “SPECIAL” section below.

MECHANICAL (GENERAL) – Provide general ventilation in processing and storage areas so that exposure limits are met.

SPECIAL – Ensure that exhaust ventilation and material transport systems involved in handling this product contain explosion relief vents or suppression systems designed and operated in accordance with applicable standards if the operating conditions justify their use.

Ingredient	OSHA Exposure Limit	ACGIH
------------	---------------------	-------

	Total	Respirable	TLV
Polyvinyl Chloride	15mg/m ³	5mg/m ³	10mg/m ³

Section 9. Physical and Chemical Properties

Appearance:	Solid Plastic Sheet
Odor:	Odorless
Odor Threshold:	N/A
PH:	Not Determined
Melting Point:	>350 °F
Initial Boiling Point/Boiling Range:	N/A
Flash Point:	(ASTM) >700 °F
Evaporation Rate:	N/A
Flammability:	N/A
Upper/lower explosive limit:	NA
Vapor Pressure:	NA
Vapor Density:	N/A
Specific Gravity:	0.45 – 1.4 g/cm ³ range
Solubility:	Not soluble in water
Partition coefficient:	N/A
Auto-Ignition:	N/A
Decomposition Temperature:	>392 °F
Viscosity:	N/A

Section 10. Stability and Reactivity

<u>Stability:</u>	Stable
<u>Substances to Avoid:</u>	Alkali's, acids and solvents
<u>Hazardous Decomposition:</u>	Hydrogen Chloride Gas, Benzene, Water, Carbon Dioxide, Metal Oxides and smoke.

Section 11. Toxicology Information

Effects of Overexposure:	
Acute:	Physical irritation of the eyes may result from overexposure to high concentrations of dust from certain fabricating operations.
Chronic:	Studies have shown that workers exposed for long periods to high concentrations of respirable PVC dust may retain the dust in their lungs. There is no evidence of a toxic response associated with such PVC dust retention.

Section 12. Ecological Information

Material is not biodegradable.
 Material is not bio accumulative
 Material is recyclable

Section 13. Disposal Information

Dispose of waste materials in accordance with Federal, State and local regulations

Section 14. Transportation

DOT: Not regulated
IMDG: Not regulated

Section 15. Regulatory Information

PROPOSITION 65: (California Only)

Sintra® products are not known to contain Prop 65 listed materials and are therefore compliant with the regulation.

REACH: Pursuant to Title II article 7 of the regulation this product is exempt from registration and notification and is therefore compliant with the REACH regulation.

RoHS: Sintra® and E-PVC™ products are compliant with the RoHS standard

TSCA: All ingredients of this product are either listed on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

CERCLA: This product does not contain ingredients which are subject to the reporting requirements of CERCLA.

SARA 313 Information: This product does not contain a chemical ingredient(s) with known CAS Number to exceed the *de minimis* reporting levels established by SARA Title III, section 313 and 40 CFR section 372 depending upon pulp inventory.

SARA 311/312 Hazard Category: This product has been reviewed according the EPA "Hazard Categories: promulgated under SARA Title III, Sections 311 and 312 and is considered, under applicable definitions, to meet the following categories:

An immediate acute) health hazard	No
A delayed (chronic) health hazard	No
A corrosive hazard	No
A fire hazard	No
A reactivity hazard	No
A sudden release hazard	No

Section 16. Other Information

IMPORTANT: The information and data contained herein are believed to be accurate and have been compiled from sources believed to be accurate. All information contained herein is offered for your consideration, information, investigation, and verification. 3A COMPOSITES MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY EXCLUDED. 3A Composites will not be responsible for claims relating to any parties' use of or reliance on information and data contained herein regardless of whether it is claimed that the information are inaccurate, incomplete, or otherwise misleading.

Definition of Common Terms:

ACGIH	=	American Conference of Governmental Industrial Hygienists
CAS#	=	Chemical Abstracts System Number
CERCLA	=	Comprehensive Environmental Response, Compensation, and Liability Act
DOT	=	U. S. Department of Transportation
DSL	=	Domestic Substance List
EPA	=	U.S. Environmental Protection Agency
IARC	=	International Agency for Research on Cancer
IATA	=	International Air Transport Association
IMDG	=	International Maritime Dangerous Goods
NA	=	Not Applicable
NIOSH	=	National Institute for Occupational Safety and Health
NTP	=	National Toxicology Program
OSHA	=	Occupational Safety and Health Administration

PEL	=	Permissible Exposure Limit
REACH	=	Registration, Evaluation, Authorization and Restriction of Chemicals
RoHS	=	Restriction of Hazardous Substances used in electronic equipment
STEL	=	Short-Term Exposure Limit (15 minutes)
TDG	=	Canadian Transportation of Dangerous Goods
TLV	=	Threshold Limit Value
TSCA	=	Toxic Substance Control Act

End of Safety Data Sheet